



Baubeschreibung

Fahrzeugwerk Bernard Krone GmbH & Co. KG, Postfach 1148, D-49753 Werlte

Business

ZZ#_Deutsche Leasing für Sparkassen
und Mittelstand GmbH
Frölingstr. 15-31
61352 Bad Homburg v. d. Höhe

Auftraggeber

Combisped
Hanseatische Spedition GmbH
Steinbrücker Str. 1
23556 Luebeck

Warenempfänger

Combisped
Hanseatische Spedition GmbH
Steinbrücker Str. 1
23556 Luebeck

Auftragsnummer / Auftragsdatum

2140291 / 15.02.2018

Bestellnummer Kunde / Bestelldatum

.

Kundennummer

Auftraggeber: 4314312

Rechnungsempfänger: 4281912

Sachbearbeiter

Mr. Johannes Möllering

Tel: +49(0)5951/209-8128

Fax: +49(0)5951/20998-8128

johannes.moellering@krone.de

Vertreter

Patric Niemann / Frank

Kosse

SDC 27 eLTU5 plus KRONE Box Liner

Menge: 50

Position: 100

T 000.001	<u>D-registration (Germany)</u>
T 000.100	Without country symbol sticker
T 001.328	Lettering on name plate: Typ: SD, certificate no. e1*2007/46*0232
T 001.339	without specifying the national registered masses on the manufacturers plate
T 001.000	TÜV standard approval:
T 001.100	Max registered king pin load: 14.000 kg
T 001.200	Max registered Axle load: 27.000 kg
T 001.300	Allowable gross vehicle weight: 40.000 kg
T 001.040	Max technical tow bar load: 14.000 kg
T 001.057	Max practical axle load: 27.000 kg Gross vehicle weight: 41.000 kg
T 500.001	Suitable for towing vehicle according to ISO 1726
T 002.301	5th wheel height unloaded: 1.020 mm

Fahrzeugwerk Bernard Krone GmbH & Co. KG · Bernard-Krone-Str. 1 · D-49757 Werlte · Postfach 1148 · D-49753 Werlte · Telefon +49(0)5951/209-0 · Telefax +49(0)5951/2465 · Internet <http://www.krone-trailer.com>

DZ Bank Hannover: IBAN DE66 2506 0000 0000 1159 32 · SWIFT-BIC GENODEFF250 · Commerzbank Lingen: IBAN DE20 2658 0070 0840 2085 00 · SWIFT-BIC DRESDEFF265
Nord/LB: IBAN DE59 2505 0000 0101 4564 73 · SWIFT-BIC NOLADE2HXXX · Volksbank Süd-Emsland eG: IBAN DE82 2806 9994 0100 4557 00 · SWIFT-BIC GENODEF1SPL

Persönlich haftende Gesellschafterin: Fahrzeugwerk Krone Verwaltungs-GmbH · Handelsregister: Amtsgericht Osnabrück HRB 210084 · Sitz der Gesellschaft: D-49757 Werlte
Geschäftsführer: Dr. Frank Albers · Bernhard Brüggem · Ralf Faust · Ingo Geerdes · Alfons B. Veer · Astrid Janke · Markus Stegen ·
Registergericht: Amtsgericht Osnabrück HRA 204937 · USt.-Id.-Nr. · St.-Nr. 53/208/37972

Combisped
Hanseatische Spedition GmbH
Steinbrücker Str. 1
23556 Luebeck

Chassis

A 100.102	Double T-longitudinal beams with cross members in welded construction
A 100.114	Step frame 120 mm
A 100.090	Chassis with pneumatic extendable rear and manual extendable front
A 100.391	Front extension with devices to locking from below
A 100.305	Neck height: 130 mm, (incl. king pin plate)
A 100.187	Interchangeable 2" kingpin, 2 positions overhang: 654 and 954 mm, mounted on 954 mm
A 100.076	Extractable Rear bumper according to EC-regulation,
A 100.072	Side guard
A 100.377	Side guard 410 mm high
A 100.375	Side guards/pallet box cove without Krone label
A 420.000	Container lockings units supporting following container types:
A 420.101	1 x 40' Container with tunnel
A 420.152	1 x 45' Container with tunnel
A 420.110	2 x 20' Container
A 420.140	1 x 20' Container lockings rear position
A 420.120	1 x 20' Container centred
A 418.004	additional container locking for 30' container flush with rear
A 420.122	Attention: Transport of full tank container is not allowed
A 420.123	Attention: Container position 20' in centre position limited to 30 tons
A 420.128	During transport of 45' containers with short tunnel the allowed length from the king pin to the rear is exceeding legal limits!
A 420.129	The transport of 45' containers with long tunnel and chamfered corners at front is possible within the EC directive. The rear bumper must be pulled out manually!
A 419.001	Height adjustable container lockings and foldable supports (for transport of 40' and 45' container without tunnel)
A 421.010	Distance kingpin - rear end: 12.000 mm at 45' containers with long tunnel 12.760 mm at 45' containers with short tunnel
A 100.029	2 rubber impact buffers at rear, central
A 100.340	Spacer plate as support for the impact buffer
A 165.003	Chequered steel plate, at rear between beams

Combisped
Hanseatische Spedition GmbH
Steinbrücker Str. 1
23556 Luebeck

Auftragsnummer: 2140291/100

Kundennummer: 4314312

Supporting legs

B 028.004 # 2 mechanically operated landing legs, 2x12 tonnes
capacity, semicircular with base plate, Brand: Jost
Series: Modul B
[TO TRANSLATE!!!]
B 001.000 Landing legs operated from right side

Axles/Suspension

C 000.004 3 axles each with a load capacity of 9.000 kg
C 143.029 Distance from kingpin to centre of axle unit = 7.915 mm
C 100.020 Axle distance: 1.410 / 1.310 mm
C 075.336 SAF axles with air suspension and Intradisc plus disc
brakes, Offset 120
C 075.965 Disc brake: Integral
C 075.960 Disc brakes 370 mm
C 043.110 With raise and lower valve, including auto reset valve, in
lowering position with fixed position
C 145.060 # SAF TIRE PILOT - Tyre Inflation System
[TO TRANSLATE!!!]

Tyres (rims)

D 410.035 6 x 435/50 R 19.5, brand Goodyear
D 185.100 Without spare wheel
D 130.091 tread: Goodyear KMAX (M+S)
D 500.002 Integrated Vehicle Tire Pressure Monitoring (IVTM), WABCO
(CAN-Connection from Trailer to Tractor ECU) * without
display at the trailer

Spare wheel carrier

E 070.000 Without spare wheel holder

Mud guards

F 002.010 Wheel covering according to EC-regulations
F 010.001 Spray suppression according to EC guideline

Brakes

G 000.103 Brake system according to ECE R 13 (incl. stability system)
G 082.000 Spring parking brake
G 079.002 Brake air pipes below beam level
G 102.010 Diagnostics by ISO7638 plug connection (EBS supply cable)
G 039.008 4 wheel chocks with holder
G 071.000 Standard ISO 1728 coupling (Palm)

Combisped
Hanseatische Spedition GmbH
Steinbrücker Str. 1
23556 Luebeck

- G 088.520 Braking system, brand: Wabco
- G 121.001 Brake lining wear information via EBS, displayed in drivers cab
- G 088.500 Attention: The trailer is only allowed on towing vehicles with compatible braking systems!
- G 085.100 EBS-braking system, 2S/2M, 2 sensors on 1 axle

Light

- H 000.001 Lights according to UN ECE Regulation No. 48
- H 070.005 2 LED outline marking lights with rubber-arm
- H 071.010 LED Side marker lights
- H 007.003 Electric connections below upper beam level
- H 001.000 24 volt, at front, with 7-channel power socket DIN ISO 1185
- H 080.000 7-channel-power socket DIN ISO 3731 at front, for add.uses
- H 060.001 Additional 15-channel-power socket at front; DIN ISO 12098
- H 060.025 socket layout with 15 pins, 9-wired main cable
- H 005.110 Multi functional rear lights, brand: Hella
- H 031.001 Including 1 fog light
- H 021.001 Including 1 reverse light
- H 045.027 2 number plate lights (LED)

Accessories

- I 010.002 2 warning plates ECE-R70 (r./y.), 565x200 mm, on rear bumper
- I 017.000 1 Orange warning plate(s), foldable (without number)

TÜV-Approval

- Z 010.002 Approval of the EC certificate of conformity according to Annex IX of Directive 2007/46/EC approval:
e1*2007/46*0232*13
- Z 000.001 registration certificate of vehicle part II

Painting

- X 000.020 Type: paint finish 40'- chassis
- X 022.000 Series painting (one colour)
- X 001.002 Steel parts are shot blasted, CDC-primer coated and powder coated
- X 090.022 Fleet number, 70 mm high, 2-sides
- X 056.010 [TO TRANSLATE!!!]
- X 056.039 White, reflective line marking on both sides, on chassis
ECE-R48, trailer type approved
- X 056.055 red, reflective line marking on chassis rear, ECE-R48

Combisped
Hanseatische Spedition GmbH
Steinbrücker Str. 1
23556 Luebeck

X 122.010 Trailer labelling according to design

1. Farbgruppe Fahrzeuge: 1

Position 10040

X 122.000 labeling
X 122.000 -Chassis
X 600.001 Clearing Labeling over the customer is nessessary
X 600.000 Designnumber: 24729
X 998.107 Chassis RAL 6017 MAY GREEN
X 998.130 Axles including hub RAL 9005 JET BLACK
X 998.242 Rear bumper/light panel WHITE POWDER COATED
X 998.890 Attachment parts BLACK OR GALVANIZED
X 998.212 Rims SILVER NATURE
X 998.272 Side guards WHITE POWDER COATED
X 998.831 Landing legs RAL 9005 JET BLACK